

#### SCOPE OF ACCREDITATION TO ISO/IEC 17025:2005

## NATIONAL TECHNICAL SYSTEMS (NTS) - LONGMONT

1601 Dry Creek Drive
Suite 2000
Longmont, CO 80503
Mr. Michael Jasiewicz Phone: 720 745 6009

#### MECHANICAL

Valid To: May 31, 2018 Certificate Number: 0214.44

In recognition of the successful completion of the A2LA evaluation process, accreditation is granted to this laboratory to perform the following <u>environmental simulation tests:</u>

### <u>Test Technology:</u> <u>Test Method(s)<sup>1,2</sup>:</u>

Vibration

Electrodynamic Shakers: MIL STD-810<sup>2</sup> (Methods 514, 519, and 526); Sine/Random/Mixed-Mode RTCA/DO-160<sup>2</sup> (Section 8);

Sine-on-Random, Random-on-Random MIL STD-202E, F, and G (Methods 201, 203,

(5 to 3000) Hz 204, and 214)

1" Stroke 18.000 lbs force

Siesmic Hydraulic Shaker:

(5 to 500) Hz 12" Stroke 12,000 lbs force

Shock

Vibration Shock – Electrodynamic Shakers: MIL STD-810<sup>2</sup> (Method 516); (5 to 3,000) Hz RTCA/DO-160<sup>2</sup> (Section 7);

1" Stroke MIL STD-202E, F, and G (Method 213)

18,000 lbs force

Up to 30 g's and 11 milliseconds

Mechanical (Drop) Shock MIL STD-810<sup>2</sup> (Method 516);

Drop Towers MIL STD-202E, F, and G (Method 213) ½ Sine, Square Wave, Trapezoidal Pulse Shape

5202 Presidents Court, Suite 220 | Frederick, MD 21703-8398 | Phone: 301 644 3248 | Fax: 240 454 9449 | www.A2LA.org

Up to 6000 g's

Down to 1 millisecond

Acceleration
R=36", 100 g's MIL-STD-810<sup>2</sup> (Method 513)

(A2LA Cert. No. 0214.44) Revised 02/28/2018

Page 1 of

### Test Technology: Test Method(s)<sup>1,2</sup>:

Temperature/Altitude

(-2,000 to 200,000) ft MIL STD-810<sup>2</sup> (Method 516); (-60 to 160) °C RTCA/DO-160<sup>2</sup> (Section 7);

RTCA/DO-160<sup>2</sup> (Section 7); MIL STD-202E, F, and G (Method 213)

Rapid Decompression MIL STD-810<sup>2</sup> (Method 500);

RTCA/DO-160<sup>2</sup> (Section 4)

High Temperature MIL STD-810<sup>2</sup> (Method 501)

To 160 °C

*Low Temperature* MIL STD-810<sup>2</sup> (Method 502)

To -100 °C

 Temperature Shock
 MIL STD-810² (Method 503);

 (-60 to 160) °C
 MIL STD-202² (Method 107)

 Temperature Humidity
 MIL STD-810² (Method 507);

 (5 to 95) %RH
 RTCA/DO-160² (Section 6);

 MIL STD-202² (Method 103)

 Temperature Cycling
 MIL STD-810² (Method 520);

 (-60 to 160) °C
 RTCA/DO-160² (Section 5)

On the following types of products: Aerospace, Military, Medical and IT Equipment

(A2LA Cert. No. 0214.44) Revised 02/28/2018

Page 2 of 2

<sup>&</sup>lt;sup>1</sup> When the date, revision or edition of a test method standard is not identified on the scope of accreditation, the laboratory is required to be using the current version within one year of the date of publication, per part C., Section 1 of A2LA *R101 - General Requirements- Accreditation of ISO-IEC 17025 Laboratories*. If a specifier/regulator imposes a different transition period, this will supersede the A2LA one-year implementation period.

<sup>&</sup>lt;sup>2</sup> Accreditation includes all final published versions of this method.



# **Accredited Laboratory**

A2LA has accredited

# **NATIONAL TECHNICAL SYSTEMS (NTS) - LONGMONT**

Longmont, CO

for technical competence in the field of

# **Mechanical Testing**

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005

General requirements for the competence of testing and calibration laboratories. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system

(refer to joint ISO-ILAC-IAF Communiqué dated 8 January 2009).



Presented this 21st day of March 2017.

President and CEO For the Accreditation Council Certificate Number 0214.44 Valid to May 31, 2018 Revised February 28, 2018

For the tests to which this accreditation applies, please refer to the laboratory's Mechanical Scope of Accreditation.