

United States Election Assistance Commission

Certificate of Conformance



ES&S EVS 5.4.1.0

The voting system identified on this certificate has been evaluated at an accredited voting system testing laboratory for conformance to the 2005 *Voluntary Voting System Guidelines (2005 VVSG)*. Components evaluated for this certification are detailed in the attached Scope of Certification document. This certificate applies only to the specific version and release of the product in its evaluated configuration. The evaluation has been verified by the EAC in accordance with the provisions of the EAC *Voting System Testing and Certification Program Manual* and the conclusions of the testing laboratory in the test report are consistent with the evidence adduced. This certificate is not an endorsement of the product by any agency of the U.S. Government and no warranty of the product is either expressed or implied.

Product Name:	EVS

Model or Version: 5.4.1.0

Name of VSTL: Pro V&V

EAC Certification Number: ESSEVS5410

Date Issued: May 23, 2018

Executive Director
U.S. Election Assistance Commission

Scope of Certification Attached

Manufacturer: *Election Systems & Software*

System Name: EVS 5.4.1.0
Certificate: ESSEVS5410

Laboratory: *Pro V&V* **Standard:** *VVSG 1.0 (2005)*

Date: May 23, 2018



Scope of Certification

This document describes the scope of the validation and certification of the system defined above. Any use, configuration changes, revision changes, additions or subtractions from the described system are not included in this evaluation.

Significance of EAC Certification

An EAC certification is an official recognition that a voting system (in a specific configuration or configurations) has been tested to and has met an identified set of Federal voting system standards. An EAC certification is **not**:

- An endorsement of a Manufacturer, voting system, or any of the system's components.
- A Federal warranty of the voting system or any of its components.
- A determination that a voting system, when fielded, will be operated in a manner that meets all HAVA requirements.
- A substitute for State or local certification and testing.
- A determination that the system is ready for use in an election.
- A determination that any particular component of a certified system is itself certified for use outside the certified configuration.

Representation of EAC Certification

Manufacturers may not represent or imply that a voting system is certified unless it has received a Certificate of Conformance for that system. Statements regarding EAC certification in brochures, on Web sites, on displays, and in advertising/sales literature must be made solely in reference to specific systems. Any action by a Manufacturer to suggest EAC endorsement of its product or organization is strictly prohibited and may result in a Manufacturer's suspension or other action pursuant to Federal civil and criminal law.

System Overview:

ES&S EVS 5.4.1.0 is comprised of the ExpressVote® (versions 2.1.0.0, and 2.1.2.0) Universal Voting System (ExpressVote), AutoMARK® Voter Assist Terminal (AutoMARK A100, A200 and A300), DS200® Precinct Digital Scanner and Tabulator (DS200), DS850® Central Count Digital Scanner and Tabulator (DS850), Electionware® Election Management System (Electionware), Election Reporting Manager® (ERM), ES&S Event Log Service (ELS), Removable Media Service (RMS), ExpressVote Previewer and VAT Previewer.

 The ExpressVote is a universal vote capture device designed for all voters, with independent voter-verifiable paper record that is digitally scanned for tabulation. This system combines paper-based voting with touch screen technology. The ExpressVote includes a mandatory vote summary screen that requires voters to confirm or revise selections prior to printing the summary of ballot selections using the internal thermal printer. Once printed, ES&S ballot scanners process the vote summary card. The ExpressVote can serve all voters, including those with special needs, allowing voters to cast ballots autonomously. ES&S has fully integrated the ExpressVote with the existing suite of ES&S voting system products.

- AutoMARK enables voters who are visually or physically impaired and voters more comfortable reading or hearing instructions and choices in an alternative language to privately mark optical scan ballots. The AutoMARK supports navigation through touchscreen, physical keypad or ADA support peripheral such as a sip and puff device or two position switch.
- DS200 digital scanner is a paper ballot tabulator designed for use as a polling place scanner. After the voter makes their selections on their paper ballot, their ballot is inserted into the unit for immediate tabulation. Both sides of the ballot are scanned at the same time using a high-resolution image-scanning device that produces ballot images.
- The DS850 is a digital scan central ballot counter that uses cameras and imaging algorithms to capture voter selections on the front and back of a ballot, evaluate results and then sort ballots into discrete bins without interrupting scanning. A dedicated audit printer generates a continuous event log. Machine level reports are produced from a second, laser printer. The scanner saves voter selections and ballot images to an internal hard disk and exports results to a USB flash drive for processing with ERM.
- Electionware integrates the election administration functionality into a unified application. Its intended use is to define an election and create the resultant media files used by the ExpressVote, DS200, AutoMARK, the DS850, and ERM. An integrated ballot viewer allows election officials to view the scanned ballot and captured ballot data sideby-side and produce ballot reports.
- ELS is a Windows Service that runs in the background of any active ES&S Election Management software application to monitor the proper functioning of the Windows Event Viewer. The ELS closes any active ES&S software application if the system detects the improper deactivation of the Windows Event Viewer.
- The ExpressVote Previewer is an application within the EMS program that allows the
 user to preview audio text and screen layout prior to burning Election Day media for the
 ExpressVote.
- The VAT Previewer is an application within the EMS program that allows the user to preview audio text and screen layout prior to burning Election Day media for the AutoMARK.
- RMS is an application that runs in the background of the EMS client workstation and supports the installation and removal of election and results media.
- ERM generates paper and electronic reports for election workers, candidates, and the media. Jurisdictions can use a separate ERM installation to display updated election totals on a monitor as ballot data is tabulated, and send the results' reports directly to the media outlets.
 - ERM supports accumulation and combination of ballot results data from all ES&S tabulators. Precinct and accumulated total reports provide a means to accommodate

candidate and media requests for totals and are available upon demand. High-speed printers are configured as part of the system accumulation/reporting stations PC and related software.

The EVS 5.4.1.0 is a modified voting system configuration that includes upgrades to the components of the EVS 5.4.0.0 and introduces a new hardware version for the ExpressVote (version 2.1.2.0). EVS 5.4.1.0 adds four new ExpressVote configuration options: Quad Express Cart, MXB ExpressVote Voting Booth, ExpressVote Single Table and ExpressVote Double Table. EVS 5.4.1.0 also: adds a new ADA table configuration for the AutoMARK; provides security upgrades to third-party EMS COTS products; and contains minor enhancements to Electionware and ExpressVote.

Mark definition:

ES&S' declared level mark recognition for the DS200 and DS850 is a mark across the oval that is 0.02" long x 0.03" wide at any direction.

Tested Marking Devices:

Bic Grip Roller Pen

Language capability:

EVS 5.4.1.0 supports English, Spanish, Chinese, Korean Japanese, and Hindi.


Components Included:

This section provides information describing the components and revision level of the primary components included in this Certification.

System Component	Software or Firmware Version	Hardware Version	Operating System or COTS	Comments
ExpressVote	2.1.1.0	2.1.0.0, 2.1.2.0		Universal Voting
(Marker)				System
ExpressVote	2.1.1.0	2.1.0.0, 2.1.2.0		Universal Voting
(Tabulator)				System
DS200	2.14.0.0	1.2.1, 1.2.3, 1.3		Precinct Digital
				Scanner and
				Tabulator
AutoMARK A100	1.8.7.0	1.0		ADA Ballot Marking
				Device
AutoMARK A200	1.8.7.0	1.1		ADA Ballot Marking
				Device
AutoMARK A200	1.8.7.0	1.3		ADA Ballot Marking
				Device
AutoMARK A300	1.8.7.0	1.3		ADA Ballot Marking
				Device
DS850	2.11.0.0	1.0		Central Count Digital
				Scanner and
				Tabulator
Ballot Box		1.2, 1.3, 1.4, 1.5		Plastic ballot box
Hardware				
Tote Bin		1.0		Plastic Tote bin

System Component	Software or Firmware Version	Hardware Version	Operating System or COTS	Comments
Collapsible Ballot Box		1.0		Collapsible ballot box
Ballot Box Hardware		1.0, 1.1, 1.2		Metal ballot box with/without diverter
EMS Reporting Workstation		Dell Optiplex 5050		Workstation for EMS Reporting
EMS Server		Dell PowerEdge T630		Server for EMS
DS850 Report Printer		OKI B430dn & Oki B431dn		Laser report printer
DS850 Audit Printer		Oki Microline 420		Dot Matrix Printer
Uninterruptible Power Supply		APC Back UPS RS 1500		APC Back UPS RS 1500
USB Flash Drive		Delkin 512MB		Storage for election and ballot definition
USB Flash Drive		Delkin 1GB		Storage for election and ballot definition
USB Flash Drive		Delkin 2GB		Storage for election and ballot definition
USB Flash Drive		Delkin 4GB		Storage for election and ballot definition
USB Flash Drive		Delkin 8GB		Storage for election and ballot definition
USB Flash Drive		Delkin 16GB		Validation purposes only
Compact Flash		Delkin Devices 512KB, 1GB, 2GB		Storage for election and ballot definition
Compact Flash Reader/Writer		Delkin 6381		
Compact Flash Reader/Writer		SanDisk 018-6305		
Barcode Scanner		DS457-SR20009		Zebra barcode scanner
Electionware	4.8.1.0			EMS software
Election Reporting Manager (ERM)	8.13.0.0			Election results reporting software
Event Log Service	1.5.6.0			Logs users' interactions with EMS
Removable Media Service (RMS)	1.4.6.0			
ExpressVote Previewer	2.1.1.0			Application within EMS
VAT Preview	1.8.7.0			Application within EMS
Adobe Acrobat Standard	11			
Cerberus FTP	9.0.3.1 (x64)			
Microsoft Server	R2 w/SP1			

System Component	Software or Firmware Version	Hardware Version	Operating System or COTS	Comments
2008				
Microsoft	64-bit/SP1			
Windows 7				
WSUS Microsoft	11.1.1			
Windows Offline				
Update Utility				
Micro Focus	12.06			
RM/COBOL				
Runtime				
Symantec Endpoint	14.0.1			
Protection				
Symantec Endpoint	20180227-001-			
Protection	core3sdsv5i64.exe			
Intelligent Updater				
Symantec Endpoint	20180226-040-IPS IU			
Protection	SEP_14RUI.exe			
Intelligent Updater				
(Network-Based				
Protection)				
Symantec Endpoint	20180225-001-SONAR			
Protection	IU_SEP.exe			
Intelligent Updater				
(Behavior-Based				
Protection)				



System Limitations

This table depicts the limits the system has been tested and certified to meet.

System Characteristic	Boundary or Limitation		Limiting Component
Max. precincts allowed in an election	9900		ERM
Max. count for any precinct element	500,000 (99,990 from an	y tabulator media)	ERM report (ERM results import)
Max. candidates allowed per election	Depends on election con maximum counters)	tent (limited by 21,000	ERM
Max. contests allowed in an election	Depends on election commaximum counters)	tent (limited by 21,000	ERM
Max. counters allowed per precinct	Limits candidates and conte to 1,000	ests assigned to a precinct	ERM
Max. contests allowed per ballot style	200 or number of positions on ballot		N/A
Max. candidates (ballot choices) allowed per contest	175		ERM (database create)
Max. number of parties allowed	General election: 75 Primary election: 20 (including nonpartisan party)		ERM (database create)
Max. 'vote for' per contest	98		ERM (database create)
Ballot formats	All paper ballots used in an election must be the same size. Votable paper ballots must contain the same number of rows.		Ballot scanning equipment
Max. Ballot Styles	9900		ERM
Max. District Types/Groups	20		ERM
Max. districts of a given type	40		
Supported Languages	EnglishSpanishChinese	KoreanJapaneseHindi	System Configuration

Product Limitations:

Paper Ballot Limitations

1. The paper ballot code channel, which is the series of black boxes that appear between the timing track and ballot contents, limits the number of available ballot variations depending on how a jurisdiction uses this code to differentiate ballots. The code can be used to

- differentiate ballots using three different fields defined as: Sequence (available codes 1-16,300), Type (available codes 1-30) or Split (available codes 1-18).
- 2. For paper ballots, if Sequence is used as a ballot style ID, it must be unique election-wide and the Split code will always be 1. In this case the practical style limit would be 16,300.
- 3. The ExpressVote activation card has a ballot ID consisting of three different fields defined as: Sequence (available codes 1-16,300), Type (available codes 1-30) or Split (available codes 1-18).

DS200

- 1. The ES&S DS200 configured for an early vote station does not support precinct level results reporting. An election summary report of tabulated vote totals is supported.
- 2. The DS200 storage limitation for write-in ballot images is 3,600 images. Each ballot image includes a single ballot face, or one side of one page.
- 3. Write-in image review requires a minimum 1GB of onboard RAM.
- 4. To successfully use the write-in report, ballots must span at least three vertical columns. Using two columns or fewer results in the write-in area being too large to print on the report tape.

AutoMARK Voter Assist Terminal

 ES&S AutoMARK capacities exceed all documented limitations for the ES&S election management, vote tabulation and reporting system. For this reason, Election Management System and ballot tabulator limitations define the boundaries and capabilities of the AutoMARK system as the maximum capacities of the ES&S AutoMARK are never approached during testing.

Electionware

- 1. Electionware capacities exceed the boundaries and limitations documented for ES&S voting equipment and election reporting software. For this reason, ERM and ballot tabulator limitations define the boundaries and capabilities of the Electionware system.
- 2. Limits were calculated using default text sizes for ballot and report elements. Some uses and conditions, such as magnified ballot views or combining elements on printed media or ballot displays, may result in limits lower than those listed. Check printed media and displays before finalizing the election.
- 3. The Electionware Export Ballot Images function is limited to 250 districts per export.
- 4. Electionware supports the language special characters listed in the System Overview. Language special characters other than those on this list may not appear properly when viewed on equipment displays or reports.
- 5. The Straight Party feature must not be used in conjunction with the single or Multiple Target Cross Endorsement features.

ExpressVote

 ExpressVote capacities exceed all documented limitations for the ES&S election management, vote tabulation and reporting system. For this reason, Election Management System and ballot tabulator limitations define the boundaries and capabilities of the ExpressVote system as the maximum capacities of the ES&S ExpressVote are never approached during testing.

Election Reporting Manager (ERM)

- 1. Election Reporting Manager requires a minimum monitor screen resolution of 800x600.
- 2. ERM Database Create allows 1600 Precincts per Ballot Style.
- 3. There is a limit of 3510 precincts in the precincts counted/not counted display.
- 4. There is a limit of 3000 precincts in the precincts counted/not counted scrolling display.
- 5. Contest/Precinct selection pop up display limited to 3000 contests/precincts.
- 6. Non-English characters are not supported in ERM. This has to do with the creation of the XML results file out of ERM.
- 7. ERM's maximum page size for reports is 5,000 pages.

Functionality

2005 VVSG Supported Functionality Declaration

Feature/Characteristic	Yes/No	Comment
Voter Verified Paper Audit Trails		
VVPAT	No	
Accessibility		
Forward Approach	Yes	
Parallel (Side) Approach	Yes	
Closed Primary		
Primary: Closed	Yes	
Open Primary		
Primary: Open Standard (provide definition of how supported)	Yes	
Primary: Open Blanket (provide definition of how supported)	No	
Partisan & Non-Partisan:		
Partisan & Non-Partisan: Vote for 1 of N race	Yes	
Partisan & Non-Partisan: Multi-member ("vote for N of M") board races	Yes	
Partisan & Non-Partisan: "vote for 1" race with a single candidate and		
write-in voting		
Partisan & Non-Partisan "vote for 1" race with no declared candidates and	Yes	
write-in voting		
Write-In Voting:		
Write-in Voting: System default is a voting position identified for write-ins.	Yes	
Write-in Voting: Without selecting a write in position.	Yes	
Write-in: With No Declared Candidates	Yes	
Write-in: Identification of write-ins for resolution at central count	Yes	

Feature/Characteristic	Yes/No	Comment
Primary Presidential Delegation Nominations & Slates:		
Primary Presidential Delegation Nominations: Displayed delegate slates	No	
for each presidential party		
Slate & Group Voting: one selection votes the slate.	No	
Ballot Rotation:		
Rotation of Names within an Office; define all supported rotation methods	Yes	
for location on the ballot and vote tabulation/reporting		
Straight Party Voting:		
Straight Party: A single selection for partisan races in a general election	Yes	
Straight Party: Vote for each candidate individually	Yes	
Straight Party: Modify straight party selections with crossover votes	Yes	
Straight Party: A race without a candidate for one party	Yes	
Straight Party: N of M race (where "N">1)	Yes	
Straight Party: Excludes a partisan contest from the straight party selection	Yes	
Cross-Party Endorsement:		
Cross party endorsements, multiple parties endorse one candidate.	Yes	
Split Precincts:		
Split Precincts: Multiple ballot styles	Yes	
Split Precincts: P & M system support splits with correct contests and	Yes	
ballot identification of each split		
Split Precincts: DRE matches voter to all applicable races.	No	
Split Precincts: Reporting of voter counts (# of voters) to the precinct split	Yes	It is possible to list the
level; Reporting of vote totals is to the precinct level		number of voters.
Vote N of M:	Yes	
Vote for N of M: Counts each selected candidate, if the maximum is not	Yes	
exceeded.		
Vote for N of M: Invalidates all candidates in an overvote (paper)	Yes	
Recall Issues, with options:		
Recall Issues with Options: Simple Yes/No with separate race/election.	No	
(Vote Yes or No Question)		
Recall Issues with Options: Retain is the first option, Replacement	No	
candidate for the second or more options (Vote 1 of M)		
Recall Issues with Options: Two contests with access to a second contest	No	
conditional upon a specific vote in contest one. (Must vote Yes to vote in		
2 contest.)		
Recall Issues with Options: Two contests with access to a second contest	No	
conditional upon any vote in contest one. (Must vote Yes to vote in 2		
contest.)		
Cumulative Voting		
Cumulative Voting: Voters are permitted to cast, as many votes as there	No	
are seats to be filled for one or more candidates. Voters are not limited to	INU	
giving only one vote to a candidate. Instead, they can put multiple votes on		
one or more candidate.		
Ranked Order Voting		
numed order voting		

Feature/Characteristic	Yes/No	Comment
Ranked Order Voting: Voters can write in a ranked vote.	No	
Ranked Order Voting: A ballot stops being counting when all ranked	No	
choices have been eliminated		
Ranked Order Voting: A ballot with a skipped rank counts the vote for the	No	
next rank.		
Ranked Order Voting: Voters rank candidates in a contest in order of	No	
choice. A candidate receiving a majority of the first choice votes wins. If no		
candidate receives a majority of first choice votes, the last place candidate		
is deleted, each ballot cast for the deleted candidate counts for the second		
choice candidate listed on the ballot. The process of eliminating the last		
place candidate and recounting the ballots continues until one candidate		
receives a majority of the vote		
Ranked Order Voting: A ballot with two choices ranked the same, stops	No	
being counted at the point of two similarly ranked choices.		
Ranked Order Voting: The total number of votes for two or more	No	
candidates with the least votes is less than the votes of the candidate with		
the next highest number of votes, the candidates with the least votes are		
eliminated simultaneously and their votes transferred to the next-ranked		
continuing candidate.		
Provisional or Challenged Ballots		
Provisional/Challenged Ballots: A voted provisional ballots is identified but	Yes	
not included in the tabulation, but can be added in the central count.		
Provisional/Challenged Ballots: A voted provisional ballots is included in	Yes	
the tabulation, but is identified and can be subtracted in the central count		
Provisional/Challenged Ballots: Provisional ballots maintain the secrecy of	Yes	
the ballot.		
Overvotes (must support for specific type of voting system)		
Overvotes: P & M: Overvote invalidates the vote. Define how overvotes are	Yes	
counted.		
Overvotes: DRE: Prevented from or requires correction of overvoting.	No	
Overvotes: If a system does not prevent overvotes, it must count them.	Yes	
Define how overvotes are counted.		
Overvotes: DRE systems that provide a method to data enter absentee	No	
votes must account for overvotes.		
Undervotes		
Undervotes: System counts undervotes cast for accounting purposes	Yes	
Blank Ballots		
Totally Blank Ballots: Any blank ballot alert is tested.	Yes	
Totally Blank Ballots: If blank ballots are not immediately processed, there	Yes	
must be a provision to recognize and accept them		
Totally Blank Ballots: If operators can access a blank ballot, there must be a	Yes	
provision for resolution.		
Networking		
Wide Area Network – Use of Modems	No	
Wide Area Network – Use of Wireless	No	

Feature/Characteristic	Yes/No	Comment
Local Area Network – Use of TCP/IP	No	
Local Area Network – Use of Infrared	No	
Local Area Network – Use of Wireless		
FIPS 140-2 validated cryptographic module		
Used as (if applicable):		
Precinct counting device	Yes	DS200
Central counting device	Yes	DS850

Baseline Certification Engineering Change Order's (ECO)

This table depicts the ECO's certified with the voting system:

Change ID	Date	Component	Description	Inclusion
			Enhance system performance	Non-DeMinimis
ECO 957	6/22/17	Dell Software Drivers	with updated drivers	Optional
				Non –DeMinimis
ECO 965	10/20/17	DS200 Plastic Ballot Box	Provide better caster support	Optional
				DeMinimis -
ECO 966	10/20/17	ExpressVote HW 1.0	Security Cover for Inno Disk	Optional
				Non –DeMinimis
ECO 967	10/6/17	Dell Software Drivers	RAID Level Configuration	Optional
				De Minimis
ECO 970	10/20/17	DS200 Blue Tote Bin	Add Tamper Cap to tie strap	Optional