

VotingWorks

Electrical Hardware Test Plan

V4.2

VWS-24003-ELHTP-01

Prepared for:

Vendor Name	<i>VotingWorks</i>
Vendor System	<i>VxSuite 4.0</i>
EAC Application No.	<i>VXS4</i>

Prepared by:



4720 Independence St.
Wheat Ridge, CO 80033
303-422-1566
www.SLICompliance.com



***Accredited by the Election
Assistance Commission (EAC)
for Selected Voting System Test
Methods or Services***



Revision History

Date	Release	Author	Revision Summary
01/24/2025	1.0	S. Ramage	Initial Release
02/10/2025	2.0	S. Ramage	Corrections
07/13/2025	3.0	S. Ramage	Retest
10/14/2025	4.0	S.Ramage	VxMarkScan only
07/22/2026	4.1	S.Ramage	Corrected date of v1.0 in this list
08/31/2026	4.2	S.Ramage	508 review and corrections

Disclaimer

The information reported herein must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

Trademarks

SLI Compliance is a registered trademark of Gaming Laboratories International, LLC.

All products and company names are used for identification purposes only and may be trademarks of their respective owners.

Copyright © 2025 by SLI Compliance®, a Division of Gaming Laboratories International LLC

This document shall not be reproduced outside of SLI Compliance without written consent.



TABLE OF CONTENTS

VOTINGWORKS	1
ELECTRICAL HARDWARE TEST PLAN	1
1 INTRODUCTION	4
1.1 QUALIFICATIONS	4
1.2 HARDWARE TEST LAB FACILITY	4
1.3 REFERENCE DOCUMENTS	4
2 PRODUCT DESCRIPTION	4
2.1 INTENDED USE	4
2.2 EQUIPMENT UNDER TEST	4
2.3 POWER REQUIREMENTS	5
2.4 SUPPORT EQUIPMENT (SE)	5
2.5 EUT SOFTWARE/FIRMWARE	6
2.6 ACCESSORIES	6
3 EQUIPMENT UNDER TEST	6
3.1 OPERATING MODES AND TEST CONFIGURATIONS	6
3.2 BLOCK DIAGRAM	8
3.3 TREATMENT OF TEST FAILURES	9
3.4 BACKUP UNIT	10
3.5 TEST DOCUMENTATION	10
4 EMC/EMI TEST REQUIREMENTS	10
4.1 ELECTROMAGNETIC EMISSIONS	10
4.1.1 <i>Radiated Electromagnetic Emissions</i>	10
4.1.2 <i>Conducted Electromagnetic Emissions</i>	11
4.2 ELECTROMAGNETIC IMMUNITY	11
4.2.1 <i>Electrostatic Disruption</i>	11
4.2.2 <i>Electromagnetic Susceptibility (Radiated RF Immunity)</i>	11
4.2.3 <i>Electrical Fast Transient (EFT)</i>	12
4.2.4 <i>Lightning Surge</i>	11
4.2.5 <i>Electrical Power Disturbance (Voltage Dips)</i>	11
4.2.6 <i>Conducted RF Immunity</i>	12
5 EMC/EMI TEST SUMMARY	12



1 INTRODUCTION

This test plan covers the EMC (Electromagnetic Compatibility) and EMI (Electromagnetic Interference) test requirements and methods for the **VotingWorks** VxSuite 4.0 voting system, hereafter known as the Equipment Under Test (EUT), to the requirements as stated in Election Assistance Commission Voluntary Voting System Guidelines Version 2.0 (EAC VVSG 2.0).

1.1 Qualifications

The EUT supplied by **VotingWorks** is representative of product produced in their volume manufacturing process.

1.2 Hardware Test Lab Facility

Element Materials Technology Denver-Longmont
1736 Vista View Drive
Longmont, Colorado 80504

1.3 Reference Documents

1. Election Assistance Commission Voluntary Voting System Guidelines 2.0
2. Election Assistance Commission Voluntary Voting System Guidelines (VVSG) v 2.0, Test Assertions v 1.3
3. NIST Handbook 150-2020
4. NIST Handbook 150-22-2021
5. Election Assistance Commission Voting System Testing and Certification Program Manual, United States Election Assistance Commission, v 3.0
6. SLI Compliance VSTL Quality System Manual, Rev. 4.1 Aug. 14, 2023

2 Product Description

2.1 Intended Use

The EUT is intended to be used in the polling place environment.

2.2 Equipment Under Test

Product/Model	Serial Number	Description	Qty
VxMarkScan	MK-11-004	VxMarkScan is an accessible ballot marking device (BMD). After Poll Worker assistance to get started, Voters use VxMarkScan to mark,	1



		verify, and cast their ballot in visual-touch, audio-tactile, and limited dexterity interaction modes. PVR is stored in bin to be scanned later. VxMarkScan does not produce cast-vote records (CVRs).	
--	--	--	--

2.3 Power

Requirement	Type
AC mains	Yes
Input Voltage Rating as it appears on unit, power supply, or power brick	100-240V
VxMarkScan - Input Current (specify @ 230 Vac/50 Hz)	2.5A
Input Current (specify @ 230 Vac/50 Hz)	6.5A
Single or Multi-Phase (If multi-phase, specify delta or wye)	Single
Input Power connector a 2-prong, 3-prong, 4 prong or 5 prong plug	3-prong
Does EUT have more than 1 power cord.	No

2.4 Support Equipment (SE)

Product/Model	Serial Number	Description	Qty
Smart Cards	TBD	Programable Smart Cards for election	3
Headphones	TBD	Optional Attachment to the VxMarkScan for user with visual impairments	1
Sip and Puff	TBD	Optional Attachment to the VxMarkScan for user with dexterity impairments	1
APC	TBD	UPS for VxMarkScan	1

2.5 EUT Software/Firmware

Name	Version	Functionality
VotingWorks Software (all)	TBD	Election software for operational status check.

2.6 Accessories

Type	Model	Function
Test Ballots	N/A	Pre-mark Test Ballots
SanDisk 64G USB	NA	Load election definitions, record CVRs and audit logs.

3 Equipment Under Test

Backup units of the same model with unique serial numbers may be used throughout EMC/EMI testing provided the following criteria are met:

- Issue with EUT.
- Identical hardware.
- All hardware components are listed in Manufacturer's Bill of Materials (BOM) or Approved Parts List (APL).

3.1 Operating Modes and Test Configurations

Prior and during testing, proper operation of the EUT shall be confirmed using **VotingWorks** software. An operational status check shall be performed prior to and after each test to fully exercise the EUT and ensure that no damage has occurred as a result of the test.

To fully exercise all the features of each product, test software is run during electrical tests to exercise the model's particular hardware features.

- VotingWorks VxMarkScan

- **USB with signed election package**
- **Election Manager Smart Card for election**
- **Poll Worker Smart Card for election**
- **APC**
- **HeadPhones**
- **Sip and Puff**
- **Privacy screen**


Setup for EMC Testing

- **Unfold stand**
- **Add tray to stand**
- **Put power brick in tray**
- **Put VxMarkScan on stand**
- **Attach Ballot Box**
- **Plug in APC to external power supply**
- **Plug in VxMarkScan to APC**
- **Power on VxMarkScan**
- **Insert HeadPhones in front jack ("primary jack")**
- **Insert sip and puff**
- **Place privacy screen around VxMarkScan**
- **Insert EM Card**
- **Insert signed election package**
- **Remove EM card / USB**

- Insert PW card
- Select Precinct
- Remove PW Card
- Place a ballot into scanner. It will repeatedly feed the same ballot (shoeshine) without fully dropping it into the box.
- Device is now ready for testing

3.2 Block Diagram

VxMarkScan Configuration





3.3 Treatment of Test Failures

Failures of electrical tests or failures of the exercising software to perform shall be documented in the electrical test report.

3.4 Backup Unit

Backup unit of the same model with unique serial numbers may be used throughout EMC/EMI testing provided the following criteria are met:

- Issue with the EUT.
- Backup unit is identical to the EUT.
- All hardware components are listed in Manufacturer's BOM or APL.

3.5 Test Documentation

A test report shall be obtained from the test lab that meets the pertinent requirements ISO/IEC17025 (E), "General Requirements for the Competence of Testing and Calibration Laboratories", 2017-11.

4 EMC/EMI Test Requirements

4.1 Electromagnetic Emissions

Objective: To verify that the electromagnetic emissions generated by the product under normal use and in the product's intended environment are below a level as specified by FCC Federal Communications Commission, Part 15; Class A or B requirements for radiated emissions by testing per ANSI C63.4-2014.

Class A is utilized for non-polling locations, and Class B is utilized for polling locations.

1.2-I – FCC Part 15 Class A and B Conformance

The voting system **MUST** comply with the Rules and Regulations of the Federal Communications Commission, Part 15; Class A or Class B requirements for radiated and conducted emissions by testing per ANSI C63.4-2014.

The voting system documentation **MUST** indicate whether devices comprising the system are intended to be located in non-polling places (Class A) or polling places (Class B).



4.1.1 Radiated Electromagnetic Emissions

Frequency Bands:

30 MHz - 1 GHz, FCC Part 15. Class B.

1 GHz - 10 GHz, FCC Part 15. Class B.

Deviations from Test Method: None

4.1.2 Conducted Electromagnetic Emissions

Frequency Bands:

150 kHz - 30 MHz, FCC Part 15. Class B.

Deviations from Test Method: None

4.2 Electromagnetic Immunity

Objective: To verify that the product performs as intended when exposed to different types of electromagnetic energies that may be encountered under normal use in the product's intended environment.

4.2.1 Electrostatic Disruption

2.7-K – Electrostatic discharge immunity

The voting system MUST be able to withstand testing in accordance with the latest IEC 61000-4-2 (2008), level 4, applying an air discharge or a contact discharge according to the nature of the enclosure of the voting system, and without damage, disruption of normal operation, or loss of data.

Application of electrostatic discharge points to COTS components MAY be performed.

The voting system may cycle power or have momentary interruption of power provided that normal operation is resumed without human intervention or loss of data.

Test Level 4:

Will not exceed the required ESD limits for all ESD test levels.

Test Location	Test Voltage +/- (kV)
Indirect Contact: HCP	8.00

Indirect Contact: VCP	8.00
Direct Contact to Metallic Surfaces	8.00
Air Discharges to Insulated Surfaces	2.00, 4.00, 8.00, 15.00

Deviations from Test Method: On the SIP and Puff input jack, wait 30 seconds between discharges and bleed off once during this time.

On all other testing, between discharges bleed off (due to DC conversion) but don't wait any additional time.

4.2.2 Electromagnetic Susceptibility (Radiated RF Immunity)

2.7-G – Electrical disturbance

The voting system MUST be able to withstand testing in accordance with the latest IEC 61000-4-3 (2020) standard for radiated immunity, without disruption of normal operation or loss of data.

Test Level 3:

Test field strength (V/m)	Frequency Range (MHz)	Modulation/Sweep
10 V/m	80 to 1000	1 kHz 80% AM, 1% steps with 3s dwell

Deviations from Test Method: None

4.2.3 Electrical Fast Transient (EFT)

2.7-I – Withstand conducted electrical disturbances

The voting system MUST be able to withstand testing in accordance with the latest IEC 61000-4-4 (2012) standard for electrical fast transient protection, without disruption of normal operation or loss of data.

Note: Repetition Rate for all transient pulses will be 100 kHz

Test Level 3:

- +2 kV and –2 kV on External Power lines (both AC and DC)
- +1 kV and –1 kV on Input/Output lines (signal, data, and control lines) longer than 3 meters
- Repetition Rate for all transient pulses will be 100 kHz

Deviations from Test Method: None

4.2.4 Lightning Surge

2.7-I – Withstand conducted electrical disturbances

The voting system MUST be able to withstand testing in accordance with the latest IEC 61000-4-5 (2014) standard for lightning surge protection, without disruption of normal operation or loss of data.

Test Levels 3-4: Differential Mode – 2kV, Level 3. Common Mode – 2kV, Level 4.

Test Voltage: +/- kV	Coupling Mode
+/- 2 kV	AC line to line (Differential Mode)
+/- 2 kV	AC line to earth (Common Mode)
+/- 0.5 kV	DC line to line >10m (Differential Mode)
+/- 0.5 kV	DC line to earth >10m (Common Mode)
+/- 1 kV	I/O signal/control >30m

Deviations from Test Method: None

4.2.5 Electrical Power Disturbance (Voltage Dips)

2.7-I – Withstand conducted electrical disturbances

The voting system MUST be able to withstand testing in accordance with the latest IEC61000-4-11 (2020) standard for power dips, interruptions, and variations immunity, without disruption of normal operation or loss of data.

Test Class 1:

Electrical Power Disturbance
Voltage dip of 30% of nominal @10 MS;
Voltage dip of 60% of nominal @100 mms & 1 sec
Voltage dip of >95% interrupt @5 sec
Surges of + 15% and – 15% line variations of nominal line voltage
Electric power increases of 7.5% and reductions of 12.5% of nominal specified power supply for a period of up to four hours at each power level

Deviations from Test Method: None

The voting system MUST not be disturbed by a temporary overvoltage of 120 % normal line voltage lasting from 3 mess to 0.5 s, applied in gradual steps of overvoltage across the line and neutral terminals.

The voting system MUST not be disturbed nor overheat for a permanent overvoltage of 10% above the nominal 120 V rating of the voting system, applied in gradual steps of overvoltage across the line and neutral terminals.

4.2.6 Conducted RF Immunity

2.7-J – Emissions from other connected equipment

The voting system MUST be able to withstand testing in accordance with the latest IEC 61000-4-6 (2013) standard for conducted immunity, without disruption of normal operation or loss of data.

Test Level 3:

Conducted RF Energy
10V rms over the frequency range 150 KHz to 80 MHz with an 80% amplitude modulation with a 1 KHz sine wave AC & DC power.
10V sig/control >3 m over the frequency range 150 KHz to 80 MHz with an 80% amplitude modulation with a 1 KHz sine wave

Deviations from Test Method: None

5 EMC/EMI Test Summary

The following Table shows the tests to be performed on the EUT.

Test	Test Specification	VVSG 2.0	Comments
Electromagnetic Emissions Tests			
Radiated Electromagnetic Emissions	FCC, Part 15 Class A/B ANSI C63.4-2014. Class B [FCC19a]	1.2-I.1, 1.2-I.2	
Conducted Electromagnetic Emissions	FCC, Part 15 Class A/B ANSI C63.4-2014. Class B [FCC19a]	1.2-I.1, 1.2-I.2	
Electromagnetic Immunity Tests			
Electrostatic Disruption	IEC 61000-4-2	2.7-K	
Electromagnetic Susceptibility	IEC 61000-4-3	2.7-G	
Electrical Fast Transient	IEC 61000-4-4	2.7-I	
Lightning Surge	IEC 61000-4-5	2.7-I	
Electrical Power Disturbance	IEC 61000-4-11	2.7-I	
Conducted RF Immunity	IEC 61000-4-6	2.7-J	



End of ELEC Hardware Test Plan
